

DATA SHEET/ U-SCREED MB PRIMER

Polyurethane moisture barrier primers are specialized coatings designed to prevent moisture damage on concrete surfaces.

KEY FEATURES

- Water-resistant: Creates a barrier that prevents water and moisture from seeping into surfaces
- Breathable: Allows moisture vapor to escape, reducing the risk of trapped moisture and related issues
- Adhesion-enhancing: Improves the bond between the surface and subsequent coatings or finishes

BENEFITS

- Prevents water damage: Reduces the risk of water-related issues, such as peeling, blistering, or mold growth
- Protects surfaces: Helps to maintain the integrity and longevity of surfaces, including walls and floors

APPLICATION AND USAGE

- Floors that are to receive MB Primer should be clean and free of grease or oily residues.
- Application method: Typically applied using a trowel or roller, such as a short-haired velour or foam roller
- Consumption: Varies depending on the product and surface type, but generally ranges from 60-100 g/m² as a primer to 150-250 g/m² as a moisture barrier
- Drying time: Is 12 hours to apply new coating or U-Screed.

TECHNICAL DETAILS

- Coverage: 15m²/kit
- Touch Dry: 3-4 hours
- Cured: 12 hours Resin
- Packaging: 2.9kg; Hardener: 2.45kg; Aggregate: 5.5kg

