



DATASHEET

KWIKRETE™ U-SCREED™ MOISTURE BARRIER (MB) PRIMER KIT

Polyurethane moisture barrier primers are specialized coatings designed to prevent moisture damage on concrete surfaces.

KEY FEATURES:

- **Water-resistant:** Creates a barrier that prevents water and moisture from seeping into surfaces
- **Breathable:** Allows moisture vapor to escape, reducing the risk of trapped moisture and related issues
- **Adhesion-enhancing:** Improves the bond between the surface and subsequent coatings or finishes

BENEFITS:

- **Prevents water damage:** Reduces the risk of water-related issues, such as peeling, blistering, or mold growth
- **Protects surfaces:** Helps to maintain the integrity and longevity of surfaces, including walls and floors



Registration Number: 2012/175489/07



PHONE: +27 21 557 7111



EMAIL: orders@kwikrete.co.za



22 McLaren Dr, Milnerton Rural, Cape Town, 7441

APPLICATION AND USAGE:

- Floors that are to receive Kwikrete™ U-Screed™ Moisture Barrier (MB) Primer should be clean and free of grease or oily residues.
- Application method: Typically applied using a trowel or roller, such as a short-haired velour or foam roller
- Consumption: Varies depending on the product and surface type, but generally ranges from 60-100 g/m² as a primer to 150-250 g/m² as a moisture barrier
- Drying time: Is 12 hours to apply new coating or U-Screed.

TECHNICAL DETAILS:

Coverage:	15m ² / KIT
Touch Dry:	3-4 Hours
Cured:	12 Hours Resin
Packaging:	2.9kg - Hardener, 2.45kg-Aggregate: 5.5kg

