

DATASHEET

KWIKRETE™ U-SCREED™ PROTECTIVE COATING

High Gloss Acrylic Floor Sealer & Protective Coating

PRODUCT DESCRIPTION:

KWIKRETE U-SCREED™ PROTECTIVE COATING is a premium water-based acrylic protective coating designed to provide a durable, high-gloss finish for decorative and industrial concrete floors. It enhances the appearance of concrete while protecting surfaces from dusting, light abrasion, stains, and everyday wear. The coating dries to a clear, tough finish that is easy to maintain and suitable for both residential and commercial applications.

RECOMMENDED USES:

Suitable for:

- Decorative concrete floors
 - Polished concrete
 - U-SCREED™ flooring systems
 - Warehouses
 - Showrooms
 - Retail stores
 - Workshops
 - Garages
 - Residential floors
 - Commercial buildings
-



Registration Number: 2012/175489/07



PHONE: +27 21 557 7111



EMAIL: orders@kwikrete.co.za



22 McLaren Dr, Milnerton Rural, Cape Town, 7441



Quality Cement Based Products • Sand • Stone • Transport



www.kwikrete.co.za

FEATURES AND BENEFITS:

- High gloss protective finish
- Water-based acrylic formulation
- Clear, non-yellowing finish
- Improves stain resistance
- Reduces concrete dusting
- Excellent adhesion to concrete
- Easy to clean and maintain
- Low odour
- Fast drying
- Suitable for interior applications

SURFACE PERPARATION:

- Ensure the surface is clean, dry, and fully cured.
- Remove dust, grease, oil, laitance, and loose material.
- Repair any cracks or defects before application.
- The surface should be free from standing water.

APPLICATION:

1. Stir thoroughly before use.
2. Apply using a mohair roller, microfiber applicator, or suitable brush.
3. Apply a thin, even coat.
4. Allow the first coat to dry before applying a second coat.
5. Two coats are recommended for optimum protection.
6. Avoid heavy traffic until the coating has fully cured.



Registration Number: 2012/175489/07



PHONE: +27 21 557 7111



EMAIL: orders@kwikrete.co.za



22 McLaren Dr, Milnerton Rural, Cape Town, 7441



TOOLS REQUIRED:

- Hamilton's Mohair roller
- Paint tray
- Hamilton's Brush for edges
- Protective gloves
- Safety glasses

CLEANING:

Clean tools immediately after use with clean water.

STORAGE:

Store in unopened containers in a cool, dry place out of direct sunlight. Protect from freezing.

SHELF LIFE:

12 months when stored correctly in original sealed packaging.

PACKAGING:

- 5 L





SAFETY PRECAUTIONS:

- Keep out of reach of children.
- Avoid contact with eyes and skin.
- Wear appropriate PPE during application.
- Ensure adequate ventilation.
- Do not ingest.
- Refer to the Safety Data Sheet (SDS) before use.

LIMITATIONS:

- For fully cured concrete only.
- Do not apply to damp surfaces.
- Protect from rain and moisture until fully cured.
- Not suitable for continuously submerged areas.

TECHNICAL DATA:

Appearance	Milky white liquid
Dry Film	Clear, glossy
Base	Water-based acrylic polymer
Finish	High Gloss
Colour	Clear
Touch Dry	20 to 30 minutes
Recoat Time	1 to 2 hours
Full Cure	24 to 48 hours
Coverage	8 to 10 m ² per litre per coat (depending on surface porosity)
Application Temperature	10°C to 30°C

