

DATASHEET

KWIKRETE™ XYLENE

PRODUCT DESCRIPTION:

KWIKRETE™ XYLENE is a clear, colorless, aromatic hydrocarbon solvent widely used in paints, coatings, adhesives, inks, and cleaning applications. It provides excellent solvency for alkyd resins, chlorinated rubber, and many synthetic polymers, making it an effective thinner and cleaning agent.

TYPICAL APPLICATIONS:

- Paint and coating thinner
- Epoxy and resin formulations
- Industrial cleaning and degreasing
- Adhesive manufacturing
- Ink production
- Solvent-based coatings

PRODUCT BENEFITS:

- Excellent solvent power
- Fast evaporation rate
- Improves flow and leveling of coatings
- Effective cleaning and degreasing properties
- Compatible with many industrial formulations



Registration Number: 2012/175489/07



PHONE: +27 21 557 7111



EMAIL: orders@kwikrete.co.za



22 McLaren Dr, Milnerton Rural, Cape Town, 7441



DIRECTIONS FOR USE:

Use as supplied or as recommended by the coating or product manufacturer. Add gradually while mixing until the desired viscosity is achieved. Always perform compatibility testing before use.

SAFETY PRECAUTIONS:

- Highly flammable liquid and vapour.
- Use only in well-ventilated areas.
- Avoid breathing vapours or mists.
- Wear suitable gloves, eye protection, and protective clothing.
- Keep away from heat, sparks, open flames, and hot surfaces.
- Store in a cool, dry, well-ventilated area.
- Keep containers tightly closed when not in use.

STORAGE:

Store in original sealed containers away from direct sunlight, ignition sources, oxidizing agents, and foodstuffs. Maintain storage temperatures between 5°C and 35°C where possible.

PACKAGING:

Available in:

- 5 Litre



Registration Number: 2012/175489/07



PHONE: +27 21 557 7111



EMAIL: orders@kwikrete.co.za



22 McLaren Dr, Milnerton Rural, Cape Town, 7441



SHELF LIFE:

24 months when stored in unopened original containers under recommended storage conditions.

TECHNICAL DETAILS:

Appearance	Clear, Colorless Liquid
Odour	Aromatic Hydrocarbon Odour
Specific Gravity @ 20°C	0.86 - 0.88
Boiling Range	137 - 144°C
Flash Point (Closed Cup)	Approximately 25°C
Solubility in Water	Insoluble
Evaporation Rate	Moderate



Registration Number: 2012/175489/07



PHONE: +27 21 557 7111



EMAIL: orders@kwikrete.co.za



22 McLaren Dr, Milnerton Rural, Cape Town, 7441